

VERSIONE SILENZIATA ⁵ SILENT VERSION

CON MOTORE: ENGINE BRAND:



MODELLO MODEL	400V 3PH Trifase Three-phase	400V 3PH Trifase Three-phase	MOTORE ENGINE							QUADRO CONTROL PANEL	L W H			Kg	dBA @7m (●)
	LTP kVA	PRP kVA	modello model	RPM		cilindri cylinders	cm ³				L cm	W cm	H cm		
DYNAMIC G10PS	10	9	403A-11G1	1500	Diesel	3	1131	70	35	QFIA-4520	190	80	123	500	66
DYNAMIC G13PS	15	13	403A-15G1	1500	Diesel	3	1496	70	25	QFIA-4520	190	80	123	550	66
DYNAMIC G15PS	17	15	403A-15G2	1500	Diesel	3	1496	70	23	QFIA-4520	190	80	123	600	66
DYNAMC G20PS*	22	20	404A-22G1	1500	Diesel	4	2216	70	18	QFIA-4520	190	80	123	704	66
STRONG G30PS*	33	30	1103A-33G	1500	Diesel	3	3300	100	19	QFIA-4520	221,3	96	125.8	950	69
STRONG G45PS	50	45	1103A-33TG1	1500	Diesel	3	3300	100	12	QFIA-4520	221,3	96	125.8	1011	66
STRONG G60PS	66	60	1103A-33TG2	1500	Diesel	3	3300	100	10	QFIA-4520	221,3	96	125.8	1067	70
KING G60PS*	66	60	1103A-33TG2	1500	Diesel	3	3300	150	14	QT2A-4520	225	105.6	170	1219	66
KING G80PS*	88	80	1104A-44TG2	1500	Diesel	4	4400	150	11	QT2A-4520	225	105.6	170	1448	66
QUEEN G100PS*	112	102	1104C-44TAG2	1500	Diesel	4	4400	270	16	QT2A-4520	295	105.6	190	1620	69
QUEEN G130PS*	149	135	1106A-70TG1	1500	Diesel	6	7010	270	12	QT2A-4520	295	105.6	190	1862	69
QUEEN G150PS*	165	150	1106A-70TAG2	1500	Diesel	6	7010	270	11	QT2A-4520	295	105.6	190	1935	69
ROYAL G180PS*	198	180	1106A-70TAG3	1500	Diesel	6	7010	350	11	QT2A-4520	360	122.6	200	2200	68
ROYAL G200PS	220	200	1106A-70TAG4	1500	Diesel	6	7010	350	10	QT2A-4520	360	122.6	200	2367	68
ROYAL G225PS	248	225	1506A-E88TAG2	1500	Diesel	6	8800	350	10	QT2A-4520	360	122.6	200	2250	68
ROYAL G250PS	275	250	1506A-E88TAG3	1500	Diesel	6	8800	350	8	QT2A-4520	360	122.6	200	2763	68
ROYAL G300PS	330	300	1506A-E88TAG5	1500	Diesel	6	8800	350	7	QT2A-4520	360	122.6	200	2705	69
MAGNUM G350PS	385	350	2206A-E13TAG2	1500	Diesel	6	12500	620	11	QT2A-4520	450	166.6	225	4109	67
MAGNUM G400PS	440	400	2206A-E13TAG3	1500	Diesel	6	12500	620	10	QT2A-4520	450	166.6	225	4730	68
MAGNUM G450PS	495	450	2506C-E15TAG1	1500	Diesel	6	15000	620	9	QT2A-4520	450	166.6	225	4597	68
MAGNUM G500PS*	550	500	2506C-E15TAG2	1500	Diesel	6	15000	620	8	QT2A-4520	450	166.6	225	4650	68
OMEGA G600PS	660	600	2806A-E18TAG1A	1500	Diesel	6	18130	950	11	QTVA-7320	450	184	254	5970	71
OMEGA G650PS	700	650	2806A-E18TAG2	1500	Diesel	6	18130	950	11	QTVA-7320	450	184	254	5970	71
EXTREME G750PS	825	750	4006-23TAG2A	1500	Diesel	6	22900	400	3	QTVA-7320	566,6	220	297	9200	71
EXTREME G800PS	880	800	4006-23TAG3A	1500	Diesel	6	22900	400	3	QTVA-7320	566,6	220	297	8800	71
EXTREME G1000PS	1133	1030	4008TAG2A	1500	Diesel	8	30600	400	2	QTVA-7320	860	220	307	11710	71
EXTREME G1260PS	1375	1250	4012-46TWG2A	1500	Diesel	12	45840	400	2	QTVA-7320	860	220	340	14100	74
EXTREME G1500PS	1650	1500	4012-46TAG2A	1500	Diesel	12	45840	400	1,7	QTVA-7320	860	220	340	14300	74
EXTREME G1700PS	1875	1688	4012-46TAG3A	1500	Diesel	12	45840	400	1	QTVA-7320	860	236	860	15000	74

LEGENDA CODICE:

LEGENDA CODICE:		LEGEND CODE:	
P	Motore PERKINS	PERKINS engine	
S	Versione silenziosa	Silent version	
*	Potenza disponibile, anche con motore conforme alla normativa emissioni, per uso mobile in Europa	Also available with emission certified engine for mobile use in Europe	
	Autonomia al 75% del carico	Autonomy at 75% load	
(●)	Valore misurato, rumorosità conforme alla direttiva 2000/14/CE	Tested value, noise level compliant with 2000/14/CE	

Sui modelli da 1000kVA in su, il Radiatore Tropicalizzato è Optional e possono esserci anche piccole variazioni nelle potenze. Per maggiori informazioni contattare ufficio commerciale.

On models from 1000kVA and up Tropical Radiator is Optional and there can also be small variation in power. For further details pls. contact sales office.

COMPLEMENTI - COMPLEMENTS

p. 26	Struttura	Structure
p. 28	Quadri	Control panel
p. 32	Quadri Automatici	ATS
p. 34	Centraline	Controllers
p. 36	Dettagli struttura	Structure details
p. 38	Accessori	Accessories
p. 42	ISO container	ISO container
p. 43	Versioni Speciali	Special Versions

